



WOODWERK

WOODWERK creates a light, simple, modern and highly durable toilet cubicle system design. Whether using a full stainless box-up or using a top rail, our first-class international standard Eco board and system design demonstrates that a restroom design is a lot more than meets the eye.



PT. INTINUSA SELAREKSA, Tbk

Office

Gedung Prosperity Lt. 51 District 8
Jl. Jend.Sudirman Kav 52 - 53
Kel. Senayan Kec. Kebayoran Baru
Jakarta 12910, Indonesia
Call : +62 21 50102788
 : +62 21 50102279



Factory

Jl. Karang Asem Timur No 27
Citeureup - Bogor 16810
Call: 021 8753966
Fax: 021 8753971

Website:
<http://intinusa.com/>



General

INTINUSA install Woodwerk Restroom Cubicle System, which is highly resistant against water and impact.

Materials

All accessories must be made of Grade 304 Stainless Steel and U channel Brackets must be made of Anodised Aluminum. Doors, Pilasters and Intermediate Partitions must have Eco Board 12mm / 19mm thick depending on the system.

Doors

All Doors shall be of 12mm or 19mm thick Eco Board. Each will be supported 3 Stainless or nylon Hinges (4 Stainless / nylon Hinges for Door width to 750mm or Door height to 2100mm) affixed to the Pilaster, completed with Stainless or Nylon Coat Hook. The standard floor clearance is 150mm.

Pilasters

All Pilasters shall be of 12mm or 19mm thick Eco Board with a router Door edge Stopper (incorporated Rubber Lining to dampen noise) affixed on one vertical side and completed with stainless Nylon Thumbturn for locking doors. The Pilaster shall be anchored to the floor using stainless or Nylon Adjustable Leg. standard Pilaster width to be 300mm and start or end Pilaster width to be 150mm for maximum stability.

Intermediate Partitions

All Intermediate Partitions shall be of 12mm or 19mm thick Eco Board with Aluminium U-channel, affixed at its ends (to the wall and pilaster).

Top Rail

The Top Rail can be easily attached to the pilaster providing maximum strength, and system alignment, as well as providing beautiful visuals.

Accessories

Each toilet cubicle will be equipped with the following accessories :

- Thumbturn stainless or Nylon with occupancy indicator.
- Stainless or Nylon Coat Hangers with rubber stoppers allow loads up to 15 kg each. Hinge Stainless comes with a unique in-place door setting mechanism which allows the door to behave normally to close fully or open at 15° - 90° intervals. This allows it to be Right or Left Hinge. (does not apply to nylon hinges)
- Stainless or Nylon Adjustable Leg with a working range from 145mm to 170mm.

Compartment's Dimension

The recommended restroom cubicle size: 800mm - 900mm x 1500mm - 1800mm x 2030mm (WxDxH).

- Door size shall be between 600mm - 700mm in width.
- Door size shall be between 800mm - 1000mm in width for disable restroom.

Colours

Standard toilet cubicle System shall be of a single colour. Colour differences from Doors, Pilasters and Intermediate Partitions are available upon request. The price will vary due to multiple color selections.

Installation

Installation will be executed by Woodwerk team shall be carried out in accordance with Woodwerk installation method.

